

MADE IN
ITALY

UK

EYEBEAM®
CONTEMPORARY WARMTH



WOOD

WOOD-EYEBEAM | WOOD-SOAP | WOOD-STAR

Design Arch. Alessandro Tesolin

EYEBEAM®
CONTEMPORARY WARMTH

EYEBEAM s.r.l.
Via A. Volta, 17 - 33082 Azzano Decimo Pordenone (Italy)
Phone +39 0434 632880 - e-mail: purchase@eyebeam.it
www.eyebeam.it



f Eyebeam - Contemporary Warmth

WOOD-EYEBEAM ELECTRIC SYSTEM



		S	M	L
Height	(mm)	1000	1220	1520
Width	(mm)	500	600	600
Weight	(kg)	11,00	15,60	19,20
Power	(watt)	700	1000	1500

WOOD-EYEBEAM HYDRONIC SYSTEM



		S	M	L
Height	(mm)	1000	1220	1500
Width	(mm)	500	600	600
Weight	(kg)	9,82	14,05	17,53
Power	(watt)	475	605	705
Water content	(l)	0,42	0,60	0,78
Couplings	Lateral (interaxis)	450	550	550
	Central (Pitch)	50	50	50

WOOD-SOAP ELECTRIC SYSTEM

		S	M	L
Height	(mm)	1380	1660	1900
Width	(mm)	500	600	600
Weight	(kg)	13,08	19,40	22,02
Power	(watt)	700	1000	1500

WOOD-SOAP HYDRONIC SYSTEM

		S	M	L
Height	(mm)	1380	1660	1900
Width	(mm)	500	600	600
Weight	(kg)	11,92	16,90	19,78
Power	(watt)	484	614	714
Water content	(l)	0,42	0,60	0,78
Couplings	Lateral (interaxis)	450	550	550
	Central (Pitch)	50	50	50

WOOD-STAR ELECTRIC SYSTEM

		S	M	L
Height	(mm)	1063	1300	1600
Width	(mm)	532	650	670
Weight	(kg)	11,80	17,00	20,80
Power	(watt)	700	1000	1500

WOOD-STAR HYDRONIC SYSTEM

		S	M	L
Height	(mm)	1063	1300	1600
Width	(mm)	532	650	670
Weight	(kg)	10,42	15,10	18,73
Power	(watt)	479	609	709
Water content	(l)	0,42	0,60	0,78
Couplings	Lateral (interaxis)	450	550	550
	Central (Pitch)	50	50	50

Remote control included in the price, supplied as standard together with the product.



Remote control

Powers calculated according to EN 442 standard. Maximum working pressure 6 Bar. 4 1/2-inch fittings gas internal thread.

N.B. It is recommended to use water loaded in the heating system only according to the relevant standards (Ö-Norm 5195 or VDI 2035).

INSTALLATION

The EYEBEAM System design radiators are supplied with European standard couplings, guaranteeing easy installation in any existing system. They mount four 1/2 "standard fittings with interaxis of 450 mm (S) or 500 mm (M - L). On request they can be delivered with central connection and 50 mm interaxis.

FLEXIBILITY

All EYEBEAM models can be installed both horizontally and vertically for a maximum adaptability to the needs of each individual environment.

SAFETY

Since the EYEBEAM System design radiators are made of tempered glass they have the highest certification for safety glass, the insertion of a plastic adhesive film allows the glass to obtain the European UNI 12600 1B1 certification with safety performance equal to those of a shatter-proof laminated glass. Their assembly also ensures an isolation level of electronic in class 2 and a protection level of IP 45 thus ensuring maximum safety even in humid environments, such as bathrooms, swimming pools, saunas etc.

Once the product has been installed, the specially designed brackets prevent inadvertent unhooking, in accordance with the German VDI 6036 safety regulations for radiators.

The finishes and colours are indicative and may undergo variations due to the printing technique.



WELLNESS



ECO-SUSTAINABILITY



SETTING
TOUCH SCREEN
(Only Electric version)



ELECTRIC
SYSTEM



HYDRONIC
SYSTEM

WOOD model

THE DESIGN RADIATORS THAT MEETS THE NEEDS
OF WARMTH AND COMFORT FOR ANY ENVIRONMENT

EYEBEAM®
CONTEMPORARY WARMTH

A perfect summary of form, style and design, the Wood model embodies its uniqueness in the Venetian Briccola wood finish. Its clean and essential design, combined with this exclusive finish, makes the WOOD model adaptable to any style and environment, giving it even more heat.

The WOOD design radiator tells a millenary history, that of the city of Venice.

Undisputed protagonists of the lagoon city, the mooring posts are first keg oak poles planted on the seabed and used to signal the waterways and tides to craft.

Characteristic of this wood is the diligent fretwork, given by holes and circles that together create evocative designs. The architects of this symphony of forms are the shipworms, molluscs which find their natural habitat right on the mooring posts, by sculpting the wood.

Every mooring post at the end of its life, after about 10/20 years, is replaced and reused to give life to this extraordinary radiator. To enhance its elegance, the black finish of the glass, baked at 650 degrees to guarantee its resistance and chromatic invariability.

WARM WELLNESS

Thanks to its heating system, the WOOD model allows to heat the environment mainly by irradiation, emitting long-wave infrared very similar to the rays emitted by the sun, which are perceived by the human body creating a condition of well-being. This advanced system also allows you to directly heat the elements in the room which in turn re-send their heat into the environment.

This procedure ensures a comfortable ambient temperature with a much lower air temperature than traditional systems, a degree less in air temperature corresponds to a saving of at least 7% of the energy consumption.

HIGH RESISTANCE

In addition to allowing the total absence of harmful emissions right from the first switch on, the choice natural materials such as glass guarantees a very high resistance to agents, ensuring maximum product invariability and allowing installation in salty environments, environments with high humidity or in the presence of chlorine.

The WOOD model can be adapted to any shape and size and can be mounted both horizontally and vertically for maximum adaptability to the needs of each individual environment.

ECO-SUSTAINABILITY

All Eyebeam ErP radiators comply with the provisions of the Ecodesign Directive 2009/125/EC and the EU Regulation 2015/1188 for environment heaters.



ACCESSORIES

Accessories such as towel bars and hangers make them perfect in the bathroom or kitchen. In the Electric System version they can be supplied with a remote control with LCD display to allow the best possible adaptation to the needs of the individual environment and user.

FINISHES

The range of the WOOD design radiator is composed of 1 black base finish on which the wood finish will be applied.



Black